



PRODUCT DESCRIPTION

DHLA4000 electric linear actuator uses 30dB low-noise plastic motor gear, maximum load can reach 4000N, maximum speed 20MM/S.

Suitable for medical, furniture, industrial and other fields. It can be installed in the automatic control system of Windows such as construction vehicles, cleaning vehicles, ships and cargo holds.

TECHNICAL PARAMETERS

Voltage	DC24~32V / DC12~19V						
No-load Speed (MM/S)	5		10		15		20
Load Pull Capacity(N)	4000		2000		1300		800
Load Push Capacity(N)	4000		2000		1300		800
Self-locking Capacity(N)	4000		2000		1300		800
Stroke Length	50-1000MM (≥800MM Stroke Max Load 2000N)						
Noise	30dB						
Motor Power	DC24V 72W DC12V 72W						
Limit Switches	Built-in						
Operating Frequency	10% max 60min. continuous use						
Operating Temperature	0°C~+40°C						
IP Grade	IP43						
Inner Tube	Aluminum Tube						
Lead Screw Type	Type T						
Mechanical Life	More than 50,000 times						

OPTIONAL CONFIGURATION

◆ Hall Sensor ◆ Magnetic Induction Switch ◆ Upper and lower limit feedback

OUTLINE DIMENSION DRAWING

